

CERTIFICATION					
CUSTOMER:	CUSTOMER NO:				
	Y.I. ORDER NO:				
	QUANTITY:				
MATERIALS OF CONSTRUCTION:	SOLENOIDS:				
HOUSING:	TYPE:				
SIDE PLATES:	VOLTAGE:				
GATE:	ENCLOSURE:				
SHAFT:					
SEAL MATERIALS:	LIMIT SWITCHES:				
HOUSING:	TYPE:				
GATE:					
SHAFT:	ENCLOSURE:				
TYPES OF ENDS:	REMARKS:				
X:					
Y:					
Z:					
DIMENSIONS ON THIS DRAWING ARE CERTIFIED CORRECT FOR THIS ORDER					

VALVE IS DESIGNED FOR 15 PSIG (MAX) INTERNAL & DIFFERENTIAL PRESSURE @250°F

-	SIZE	А	В	С	D	E	F	F1	G	Η	J	К	L	Μ	N	Р	WEIGHT LBS C/S
-	2	21.00	14.25	6.75	4.00	8.75	9.25	9.25	4.38	13.12	-	6.00	4.75	2.00	(4) .75	.25	69
	3	25.75	17.62	8.12	4.00	9.50	9.25	9.25	4.19	13.69	-	7.50	6.00	3.00	(4) .75	.38	104
-	4	28.62	20.38	8.25	4.00	10.75	11.00	11.00	5.44	16.19	-	9.00	7.50	4.00	(8) .75	.38	158
	5	31.25	22.75	8.50	4.00	12.06	11.00	11.00	6.25	18.31	-	10.00	8.50	5.00	(8) .88	.50	248
-	6	34.25	25.50	8.75	4.00	13.25	11.00	11.00	6.77	20.01	-	11.00	9.50	6.00	(8) .88	.50	358
-	8	39.50	30.50	9.00	4.00	17.06	8.38	8.38	8.81	25.88	-	13.50	11.25	8.00	(8) .88	.50	545
\dashv	10	48.00	36.75	11.25	6.00	18.62	8.38	8.38	9.81	28.44	-	16.00	14.25	10.00	(12) 1.00	.50	745
	12	52.00	40.50	11.50	6.00	22.12	11.88	11.88	10.81	32.94	-	19.00	17.00	12.00	(12) 1.00	.50	922

NOTES:

- HOUSING, SIDE PLATES, AND GATE ARE OF CAST CONSTRUCTION. AVAILABLE IN IRON, ALUMINUM, STEEL AND STAINLESS STEEL
- ALL VALVES ARE FURNISHED WITH PLAIN ENDS IN PIPE SIZE. (STANDARD) OPTIONAL ENDS AVAILABLE ARE TUBING SIZE, AND WITH FLANGES.
- 3. HOUSINGS ARE DESIGNED FOR 15 PSI MAX AT 250 DEGREES F.
- 4. RIGHT HAND ASSEMBLY IS SHOWN WITH SIDE BRANCH 'Z' ON RIGHT SIDE AND ACTUATOR ON NEAR SIDE, LEFT HAND ASSEMBLY IS WITH SIDE BRANCH 'Z' ON LEFT SIDE AND ACTUATOR ON NEAR SIDE

' '	REVISIONS
	CUSTOMER
	CUST. NO.
	YOUNG ORDER NO.
	YOUNG INDUSTRIES MODEL 'B' SWING GATE DIVERTER VALVE MANUALLY ACTUATED STANDARD DIMENSION SHEET
	THE
GENERAL TOLERANCES	industries, inc.
VIDA VIDA VIDA VIDA DE CIEID THE EOU OWING STALL ADDIV	MUNCY, PENNSYLVANIA 177.56

GENERAL TOLERANCES

UNLESS OTHERWISE SPECIFIED THE FOLLOWING SHALL APPLY

MACHINING - .XX= .02 .XXX= .005 ANGLE= .50°

SURFACE ROUGHNESS HEIGHT 63 MICROINCHES OR LESS

FABRICATION - UNDER 6 6 TO 24 24 TO 60 OVER 60

± .06 ± .12 ± .19 ± .25

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES

INDUSTRIES, INC.

MUNCY, PENNSYLVANIA 17756
TELEPHONE: 570-546-3165

DRAWN BY: BMF

DATE DRAWN: 4/13/16