

CERTIFICATION								
CUSTOMER:	CUSTOMER NO:							
	Y.I. ORDER NO:							
	QUANTITY:							
MATERIALS OF CONSTRUCTION:	SOLENOIDS:							
HOUSING:	TYPE:							
SIDE PLATES:	VOLTAGE:							
GATE:	ENCLOSURE:							
SHAFT:								
SEAL MATERIALS:	LIMIT SWITCHES:							
HOUSING:	TYPE:							
GATE:								
SHAFT:	ENCLOSURE:							
TYPES OF ENDS:	REMARKS:							
X:								
Y:								
Z:								
DIMENSIONS ON THIS DRAWING ARE CERTIFIED CORRECT FOR THIS ORDER PER:								
								VALVE IS DESIGNED FOR 15 PSIG (MAX) INTERNAL & DIFFERENTIAL PRESSURE @250°F

SIZE	Α	В	С	D	Е	F	F1	G	Н	J	L	М	N	Р	WEIGHT LBS C/S
2	17.69	13.00	6.44	6.50	4.00	15.62	8.75	4.38	19.94	ı	6.00	4.75	(4) .75	.25	60
3	19.88	13.00	8.62	6.50	4.00	16.00	9.50	4.69	20.69	-	7.50	6.00	(4) .75	.38	95
4	23.12	15.56	9.62	7.78	4.00	18.50	10.75	5.44	23.94	-	9.00	7.50	(8) .75	.38	145
5	24.12	16.75	9.62	8.38	4.00	19.25	12.06	6.25	25.50	-	10.00	8.50	(8) .88	.50	235
6	25.62	18.25	9.62	9.12	4.00	20.00	13.25	6.81	26.81	-	11.00	9.50	(8) .88	.50	345
8	28.00	21.25	9.81	10.62	4.00	23.50	17.06	8.81	32.31	-	13.50	11.75	(8) .88	.50	520
10	34.81	25.62	12.62	12.81	6.00	24.50	18.62	9.81	34.31	-	16.00	14.25	(12) 1.00	.50	720
12	36.12	26.88	12.88	13.44	6.00	25.50	22.12	10.81	36.31	_	19.00	17.00	(12) 1.00	.50	870

NOTES:

- 1. HOUSING, SIDE PLATES, AND GATE ARE OF CAST CONSTRUCTION. AVAILABLE IN IRON, ALUMINUM, STEEL AND STAINLESS STEEL
- ALL VALVES ARE FURNISHED WITH PLAIN ENDS IN PIPE SIZE. (STANDARD) OPTIONAL ENDS AVAILABLE ARE TUBING SIZE, AND WITH FLANGES.
- 3. HOUSINGS ARE DESIGNED FOR 15 PSI MAX AT 250 DEGREES F.

FLANGED CONNECTION, ANSI 150# DRILLING (OPTIONAL)

4. RIGHT HAND ASSEMBLY IS SHOWN WITH SIDE BRANCH 'Z' ON RIGHT SIDE AND ACTUATOR ON NEAR SIDE. LEFT HAND ASSEMBLY IS WITH SIDE BRANCH 'Z' ON LEFT SIDE AND ACTUATOR ON NEAR SIDE

REV. NO.	DESCRIPTION	DATE	В
	REVISIONS		
CUSTOMER			
CUST. NO.			
YOUNG ORDE	 R NO.		

YOUNG ORDER NO. YOUNG INDUSTRIES MODEL 'C' SWING GATE DIVERTER VALVE PNEUMATIC ACTUATED STANDARD DIMENSION SHEET

GENERAL TOLERANCES UNLESS OTHERWISE SPECIFIED THE FOLLOWING SHALL APPLY MACHINING - .XX= .02 .XXX= .005 ANGLE= .50° SURFACE ROUGHNESS HEIGHT 63 MICROINCHES OR LESS FABRICATION - UNDER 6 6 TO 24 24 TO 60 OVER 60 CHECKED BY: ± .06 ± .12 ± .19 ± .25 DRAWING UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES

L O.D.

M B.C.

I.D.

industries, MUNCY, PENNSYLVANIA 17756 TELEPHONE: 570-546-3165 DATE DRAWN: 3/28/16 DRAWN BY: BMF SCALE: REV: S-4-6325