



——(12) - **P** DIA. THRU HOLES M O.D. B.C.

ROUND OUTLET FLANGE DETAIL SIZES 10" & 12" ONLY 150 # ANSI DRILLING





Size	Α	В	С	D	E	F	G	Н	J	K	L	M	N	Р	Q	R	S	Т	U	V
4	14.50	3.00	11.50	.25	8.12	4.44	4.50	5.59	5.09	2.12	9.00	7.50	4	.75	7.50	4.00	.62	3.12	-	8
5	17.25	3.00	14.25	.25	10.06	4.94	4.94	5.59	6.28	2.62	10.00	8.50	5	.88	8.50	5.00	.62	3.62	-	8
6	17.75	3.00	14.75	.25	10.44	5.44	5.44	5.59	7.50	3.12	11.00	9.50	6	.88	9.50	6.00	.62	4.12	-	8
8	21.00	3.00	18.00	.38	12.75	6.88	6.88	7.72	10.12	4.19	13.50	11.75	8	.88	11.50	8.00	.62	5.12	2.56	16
10	25.00	3.50	21.50	.38	15.19	7.88	7.88	7.72	12.53	5.19	16.00	14.25	10	1.00	14.75	10.00	1.00	6.38	6.38	16
12	29.00	4.38	24.62	.38	17.38	8.88	8.88	7.72	14.94	6.19	19.00	17.00	12	1.00	16.75	12.00	1.00	7.38	3.69	16

NOTES:

- VALVES ARE OF FABRICATED CONSTRUCTION AND AVAILABLE IN STEEL, ALUMINUM OR STAINLESS STEEL.
- 2. VALVES ARE AVAILABLE WITH ROUND OR SQUARE FLANGED ENDS, OR PLAIN ENDS.
- RIGHT HANDS ASSEMBLY IS SHOWN WITH SIDE BRANCH 'Z' ON LEFT SIDE AND ACTUATOR ON NEAR SIDE. LEFT HAND ASSEMBLY IS WITH SIDE BRANCH 'Z' ON RIGHT SIDE AND ACTUATOR ON NEAR SIDE. (RIGHT HAND ASSEMBLY IS STANDARD)

REV. NO.	DESCRIPTION	DATE	BY					
	REVISIONS							
CUSTO	MER							
CUST.	NO.							
YOUNG	G ORDER NO.							
YOUNG INDUSTRIES MODEL 'TDV' BLADE DIVERTER VALVE, 45 DEGREE, W/ PNEUMATIC ACTUATOR, STANDARD DIMENSION SHEET								

GENERAL TOLERANCES UNLESS OTHERWISE SPECIFIED THE FOLLOWING SHALL APPLY MACHINING - .XX= .02 .XXX= .005 ANGLE= .50° DRAWN BY: BMF SURFACE ROUGHNESS HEIGHT 63 MICROINCHES OR LESS FABRICATION - UNDER 6 6 TO 24 24 TO 60 OVER 60 ± .06 ± .12 ± .19 ± .25

INDUSTRIES, MUNCY, PENNSYLVANIA 17756 TELEPHONE: 570-546-3165 DATE DRAWN: 4/14/16

REV:

CHECKED BY: SCALE: 1:3 DRAWING

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES S-4-6871