

ROUND INLET & OUTLET FLANGE DETAIL SIZES 4" THRU 8" ONLY 150# ANSI DRILLING

V - .56 DIA. THRU HOLES

R - SQ.

Q - SQ.

SQUARE INLET & OUTLET FLANGE DETAIL

(8) 1.00" DIA. THRU HOLES

(4) THREADED ROD,


.88"-9UNC X 2.12" LG.,

SPACED AS SHOWN


ROUND INLET FLANGE DETAIL

SIZES 10" & 12" ONLY

150# ANSI DRILLING




ROUND OUTLET FLANGE DETAIL SIZES 10" & 12" ONLY 150# ANSI DRILLING



| | | | | | | | | | | | | | | | | | , | | |
|------|-------|------|-------|------|-------|------|------|------|------|-------|-------|-------|------|-------|-------|------|------|------|-------|
| SIZE | А | В | С | D | Е | F | G | Н | J | L | М | N | Р | Q | R | S | Т | U | V |
| 4 | 12.69 | 3.00 | 9.19 | 0.25 | 13.00 | 4.44 | 4.50 | 5.59 | 3.00 | 9.00 | 7.50 | 4.00 | 0.75 | 7.50 | 4.00 | 0.62 | 3.12 | - | 8.00 |
| 5 | 13.69 | 3.31 | 9.69 | 0.25 | 13.69 | 4.94 | 5.00 | 5.59 | 3.69 | 10.00 | 8.50 | 5.00 | 0.88 | 8.50 | 5.00 | 0.62 | 3.62 | - | 8.00 |
| 6 | 14.69 | 3.62 | 10.19 | 0.25 | 14.38 | 5.44 | 5.50 | 5.59 | 4.38 | 11.00 | 9.50 | 6.00 | 0.88 | 9.50 | 6.00 | 0.62 | 4.12 | - | 8.00 |
| 8 | 17.31 | 3.00 | 13.50 | 0.38 | 19.09 | 6.88 | 6.94 | 7.72 | 5.94 | 13.50 | 11.75 | 8.00 | 0.88 | 11.50 | 8.00 | 0.62 | 5.12 | 2.56 | 16.00 |
| 10 | - | - | - | 0.38 | - | 7.88 | 7.94 | 7.72 | - | 16.00 | 14.25 | 10.00 | 1.00 | 14.75 | 10.00 | 1.00 | 6.38 | 3.19 | 16.00 |
| 12 | - | - | - | 0.38 | - | 8.88 | 8.94 | 7.72 | - | 19.00 | 17.00 | 12.00 | 1.00 | 16.75 | 12.00 | 1.00 | 7.38 | 3.69 | 16.00 |



- VALVES ARE OF FABRICATED CONSTRUCTION AND ARE AVAILABLE IN STEEL, STAINLESS STEEL OR ALUMINUM.
- 2. VALVES ARE AVAILABLE WITH ROUND OR SQUARE FLANGED ENDS OR PLAIN ENDS.
- 3. RIGHT HAND ASSEMBLY IS SHOW WITH SIDE BRANCH 'Z' ON LEFT SIDE AND ACTUATOR ON NEAR SIDE. LEFT HAND ASSEMBLY IS WITH SIDE BRANCH 'Z' ON RIGHT SIDE AND ACTUATOR ON NEAR SIDE. (RIGHT HAND ASSEMBLY IS STANDARD)



| | REV. NO. | | | | DATE | BY | | | |
|--|---|------------|------|----------|-----------------|------|--|--|--|
| | REVISIONS | | | | | | | | |
| | CUSTOMER: * | | | | | | | | |
| | CUSTOMER PO NUMBER: * | | | | | | | | |
| | YOUNG JOB NUMBER: * TITLE YOUNG INDUSTRIES MODEL 'TDV' BLADE DIVERTER VALVE, 45 DEGREE SYMMETRICAL, W/ PNEUMATIC ACTUATOR STANDARD DIMENSION SHEET | | | | | | | | |
| | | | | | | | | | |
| | THE | | | | | | | | |
| GENERAL TOLERANCES UNLESS OTHERWISE SPECIFIED THE FOLLOWING SHALL APPLY | INDUSTRIES, INC. MUNCY, PENNSYLVANIA 17756 TELEPHONE: 570-546-3165 | | | | | | | | |
| MACHININGXX= .02 .XXX= .005 ANGLE= .50° SURFACE ROUGHNESS HEIGHT 63 MICROINCHES OR LESS | DRA | WN BY: BMF | | DATE DRA | AWN: 5/2 | 2/17 | | | |
| FABRICATION - UNDER 6 6 TO 24 24 TO 60 OVER 60 ± .06 ± .12 ± .19 ± .25 | CHECKED BY: SCALE=1:3 | | | | | | | | |
| ± .06 ± .12 ± .19 ± .25 UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES | DRAWII NUMBE | | -788 | 9 | SHEET 1 OF 1 | REV: | | | |
| | • | | | ' | | | | | |